

Category	Item #	Item Type	Notes	Description
8K Cameras				
Camera - Network	TNB-9000	8K Network Box Camera	Special Order / Please Contact HTA Sales to confirm Lead Time	43.3mm full-frame CMOS image sensor, Max. 15fps@8K, 20fps@24MP, 30fps@15MP, 60fps@4K. Compatible with Canon EF mount lens. Intelligent video analytics based on AI Object detection/classification. Attribute, BestShot, HDMI (1000p/30ps) Video Output, H.265/264 Main/H.264 MJPEG, Single Micro SD slot (up to 256GB), WiseStream II support, RJ-45, SFP slot (10/100Mbps), HPE/Ethernet 3G+ Class5, 12VDC, AI based analytics.
4K Cameras & up				
Camera - Network	PNM-9322VOP	5 Channel 2MP / 5MP X 4 + 2MP 32x PTZ		Network varidial outdoor camera that combines Multi-sensor Multi-Directional camera, (2MP/5MP X 4 sensors sold separately) 5MP -20MP (2MP @ 60fps or 5MP @30fps) fixed focal lens modules and 2MP 32x optical zoom PTZ, 4x lens code H.265H/264 MJPEG with WiseStream II technology, WDR 150dB @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, 4x SD card, halway view, H.LC, defog detection, DIS(Gyro Sensor), Audio I/O (PTZ ch only), HPE injector (included), IP66/IP68, -40°C ~ +55°C (-40°F ~ +131°F), White color, 2MP Lens modules: SLA-2M2000Z (2.8mm), SLA-2M2000 (2.8mm), SLA-2M3000 (2.8mm), SLA-2M3000Z (2.8mm), SLA-2M4000 (2.8mm), SLA-2M4000Z (2.8mm), SLA-2M5000 (2.8mm), SLA-2M5000Z (2.8mm), SLA-2M6000 (2.8mm), SLA-2M6000Z (2.8mm), SLA-2M7000 (2.8mm), SLA-2M7000Z (2.8mm)
Camera - Network	PNM-9084GZ	2MP X 4 outdoor Dome, PTRZ		Wisenet P series network varidial outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 5MP @ 60fps, motorized varifocal lens 2x (2.8-9.4mm) (102°-38.7°) PTZ (Pan/Tilt/Zoom) lens, remote adjustment, triple code H.265H/264 MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true DN, 4x SD card, halway view, H.LC, defog detection, B-Directional Audio, Alarm I/O, HPE injector (included), IP66/IP68, -40°C ~ +55°C (-40°F ~ +131°F), White color, 2MP Lens modules: SLA-2M2000Z (2.8mm), SLA-2M2000 (2.8mm), SLA-2M3000 (2.8mm), SLA-2M3000Z (2.8mm), SLA-2M4000 (2.8mm), SLA-2M4000Z (2.8mm), SLA-2M5000 (2.8mm), SLA-2M5000Z (2.8mm), SLA-2M6000 (2.8mm), SLA-2M6000Z (2.8mm), SLA-2M7000 (2.8mm), SLA-2M7000Z (2.8mm)
Camera - Network	PNM-9084RZ	2MP X 4 outdoor Dome, PTRZ w/IR		Wisenet P series network varidial outdoor Multi-sensor Multi-Directional dome camera, (2MP X 4 sensors) 5MP @ 60fps, motorized varifocal lens 2x (2.8-9.4mm) (102°-38.7°) PTZ (Pan/Tilt/Zoom) lens, remote adjustment, triple code H.265H/264 MJPEG with WiseStream II technology, 120dB WDR, defocus detection, built in analytics, true DN, 4x SD card, halway view, H.LC, defog detection, B-Directional Audio, Alarm I/O, HPE injector (included), IP66/IP68, -40°C ~ +55°C (-40°F ~ +131°F), White color, 2MP Lens modules: SLA-2M2000Z (2.8mm), SLA-2M2000 (2.8mm), SLA-2M3000 (2.8mm), SLA-2M3000Z (2.8mm), SLA-2M4000 (2.8mm), SLA-2M4000Z (2.8mm), SLA-2M5000 (2.8mm), SLA-2M5000Z (2.8mm), SLA-2M6000 (2.8mm), SLA-2M6000Z (2.8mm), SLA-2M7000 (2.8mm), SLA-2M7000Z (2.8mm)
Camera - Network	PNM-9085RZ	5MP X 4 outdoor Dome, PTRZ w/IR		5MP X 4ch multi-directional camera, Motorized PTRZ support, Max. 30fps@5MP(H.265, H.264), 4.13-9.4mm(2.3x) motorized varifocal lens, IR viewable length -30m, H.265, H.264, MJPEG code, Multi-streaming, Video analytics, WiseStream II, IP66, K10, NEMA4X
Camera - Network	PNM-9000GB	Remote head 2MP X 4CH camera		WNT multi-head camera, 4x 2MP @ 30fps, triple code H.265H/264 MJPEG, extreme WDR 150dB, dual SD cards slots, WiseStream II, halway view, H.LC, defog detection, audio I/O, HDMI out 12VDC/PoE+, DIS support, analytics-defocus, directional, motion, enter/exit, temperature, vertical lens, I/O input, Compatible with SLA-14880A/14880V/A, SLA-14880A/14880V/A, SLA-14880A/14880V/A
Camera - Network	PNM-9002VQ	2MP / 5MP X 4	Wisenet 5.0c	Network varidial outdoor Multi-sensor Multi-Directional dome camera, (2MP/5MP X 4 sensors) 5MP -20MP (2MP @ 60fps or 5MP @ 30fps), fixed focal lens modules, triple code H.265H/264 MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, halway view, H.LC, defog detection, DIS(Gyro Sensor), PoE+, IP66/IP68, K10, H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNM-9002VS	Stainless Steel Multi-sensor Dome	Special order only (10 week lead time)	Stainless steel outdoor multi-sensor dome camera, (2MP/5MP X 4 sensors) 5MP -20MP (2MP @ 60fps or 5MP @ 30fps), fixed focal lens modules, triple code H.265H/264 MJPEG with WiseStream II technology, 150dB WDR @ 2MP or 120dB @ 5MP, defocus detection, built in analytics, PTZ handover, 4x SD card, halway view, H.LC, defog detection, DIS(Gyro Sensor), PoE+, IP66/IP68, K10, H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNM-9000VD	5MP X 2 outdoor Dome		Network varidial outdoor Multi-sensor Multi-Directional dome camera, (5MP X 2 sensors) 10MP @ 30fps, modular lenses from 3.7-4.8 and 7.0mm lenses, triple code H.265H/264 MJPEG with WiseStream II technology, 120dB WDR, built in analytics, 2x SD card, halway view, H.LC, defog detection, DIS, PoE, IP66/K10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	PNM-9082VT	3CH X 2MP		Powered by WNT, 2MP X 3CH X 2MP, Multi-Directional dome camera, 3-6mm motorized varifocal lens, donut shape bubble, max 321° coverage, triple code H.265H/264 MJPEG, WiseStream II, extreme WDR 150dB, defocus detection, video analytics, 2x micro SD card, PoE+, IP66, K10, NEMA4X, operating lens -40°C~+55°C
Camera - Network	PNM-7002VD	2MP X 2 outdoor Dome	Wisenet 5.0c	Network varidial outdoor Multi-sensor Multi-Directional dome camera, (2MP X 2 sensors) 5MP -20MP (2MP @ 60fps or 5MP @ 30fps), fixed focal lens modules, triple code H.265H/264 MJPEG with WiseStream II technology, 150dB WDR, built in analytics, 4x SD card, halway view, H.LC, defog detection, DIS, PoE, IP66/K10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	PNM-9031RV	19MP Panoramic Camera		Network varidial outdoor Multi-sensor dome camera, panoramic view with stitched image, (5MP X 4 sensors) 15MP @ 20fps, triple code H.265H/264 MJPEG with WiseStream II technology, WDR 120dB, IR viewable length 20m (65.7'), built in video analytics and sound classification, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNM-9022V	8.3MP Panoramic Camera		WNT Panoramic Multi-sensor camera, 180° view, (2MP X 4 sensors) 7.3MP @ 30fps, panoramic 209° view, 8.3MP, triple code: H.265H/264 MJPEG with WiseStream II technology, extreme WDR 120dB, defocus detection, built in analytics, Heatmap, Micro View for easy installation, 2x micro SD cards, PoE+, IP66/K10/NEMA4X
Camera - Network	PND-A9081RF	4K IR Indoor Flush Mount Dome AI Camera		4K Network AI IR Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), Olux (BW, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PND-A9081RV	4K IR Indoor Vandal Dome AI Camera		4K Network AI IR Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), Olux (BW, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNV-A9081R	4K IR Outdoor Vandal Dome AI Camera		4K Network AI IR Vandal Dome Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), Olux (BW, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNO-A9081R	4K IR Bullet AI camera		4K Network AI IR Bullet Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), Olux (BW, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	PNB-A9001	4K Box AI camera		4K Network AI IR Box Camera, Max. 4K resolution, 0.05Lux@F1.6 (Color), Olux (BW, IR LED on), Day & Night(ICR), WDR(120dB), H.265, H.264, MJPEG code, WiseStream II, Video Analytics based on AI Object detection and classification(Person, Face, Vehicle, License Plate), Attribute, BestShot, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, POE+, Face Mask Detection, Social Distancing Detection
Camera - Network	XNP-9300RW	4K IR, Wiper PTZ		Powered by WNT, 4K @ 30FPS resolution, 5mm-150mm (30x) lens, built in wiper and adaptive WDR (200m), extreme WDR 120dB, H.LC, H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target track track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, K10(Camera body only), NEMA4X, HPE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-9250R	4K, 25x, IR PTZ camera		Powered by WNT, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, adaptive WDR (200m), extreme WDR 120dB, Day & Night(ICR), H.LC, H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target track track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, K10(Camera body only), NEMA4X, HPE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-9250	4K, 25x PTZ camera		Powered by WNT, 4K @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night(ICR), H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target track track, B.LC, H.LC, SSDR, IP66, K10, NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), Power, PoE+, (Compatible with IO Box SPM-4210)
Camera - Network	XNO-9082R	4K IR Bullet Camera		Wisenet X series network IR bullet camera, 4K (BMP Max) @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-9082R	4K IR Outdoor Vandal Dome		Wisenet X-plus series network IR varidial outdoor camera, 4K (BMP Max) @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-9082RF	4K IR Flush Mount Dome		Wisenet X-plus series network IR flush mount camera (plenum), 4K (BMP Max) @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-9082RV	4K IR Indoor Dome		Wisenet X-plus series network IR varidial indoor camera, 4K (BMP Max) @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNB-9002	4K Box Camera		Wisenet X series network box camera, 4K (BMP Max) @ 30fps, triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C ~ +55°C (-14°F ~ +131°F)
Camera - Network	XNF-9010RS	12MP Stainless Steel IR Fisheye Camera	Special Order / Please Contact HTA Sales to confirm Lead Time	Stainless steel fisheye, powered by WNT, 1/2.3" 12MP CMOS, max resolution 3000x3000 @ 30FPS, 1.0mm total focal lens, 360° graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG code supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR 120dB, WiseStream II support, Wide IR, viewable length 28.2 (9m), Virtual channel support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Nylion dome, Handover, IP66/IP68, K10/NEMA4X, PoE+, IP52, K10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNF-9010RV	12MP, WNT Fisheye		Powered by WNT, 1/2.3" 12MP CMOS, max resolution 3000x3000 @ 30FPS, 1.0mm total focal lens, 360° graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG code supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR 120dB, WiseStream II support, Wide IR, viewable length 32.8 (10m), Virtual channel support, Plug-in support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coded dome cover, Handover, IP66/IP68, K10/NEMA4X, PoE+, IP52, K10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNF-9010RVM	12MP, WNT Fisheye	Special Order	Powered by WNT, 1/2.3" 12MP CMOS, max resolution 3000x3000 @ 30FPS, 1.0mm total focal lens, 360° graphic type lens, enhanced resolution for the peripheral regions, H.265, H.264, MJPEG code supported, Fisheye, Single panorama, Double panorama, Quad view, On board dewarping, Digital PTZ, extreme WDR 120dB, WiseStream II support, Wide IR, viewable length 32.8 (10m), Virtual channel support, Plug-in support, selectable I/O port, Video Analytics, Heatmap, People counting, Queue management, Hard coded dome cover, Handover, IP66/IP68, K10/NEMA4X, PoE+, IP52, K10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	ZNF-9010	12MP Indoor fisheye		Wisenet Q series network indoor fisheye dome camera, 12MP CMOS sensor, max resolution 3000x3000 @ 30fps, triple code: H.265H/264 MJPEG with WiseStream II technology, WDR 120dB, business analytics (Heatmap and people counting), built-in SD card slot, PoE
6MP Cameras				
Camera - Network	XNP-9300RW	6MP IR, Wiper PTZ		Powered by WNT, 6MP @ 30FPS resolution, 5mm-150mm (30x) lens, built in wiper and WDR (200m), extreme WDR 120dB, Day & Night (ICR), H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target track track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, K10(Camera body only), NEMA4X, HPE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-9250R	6MP, 25x, IR PTZ camera		Powered by WNT, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, WDR (200m), extreme WDR 120dB, Day & Night (ICR), H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target track track, B.LC, H.LC, SSDR, lens heater for water/snow removal, IP66, K10(Camera body only), NEMA4X, HPE injector included, (Compatible with IO Box SPM-4210)
Camera - Network	XNP-9250	6MP, 25x PTZ camera		Powered by WNT, 6MP @ 30FPS resolution, 5mm-125mm (25x) lens, extreme WDR 120dB, Day & Night (ICR), H.265, H.264, MJPEG code support, Intelligent Analytics, Object auto tracking (Person/Vehicle), Target track track, B.LC, H.LC, SSDR, IP66, K10, NEMA4X, NEMA-TS 2 (2.2.8, 2.2.9), Power, PoE+, (Compatible with IO Box SPM-4210)
Camera - Network	XNO-9082R	6MP IR Bullet Camera		Wisenet X series network IR bullet camera, 6MP @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-9082R	6MP IR Outdoor Vandal Dome		Wisenet X-plus series network IR varidial outdoor camera, 6MP @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-9082RF	6MP IR Flush Mount Dome		Wisenet X-plus series network IR flush mount camera (plenum), 6MP @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XND-9082RV	6MP IR Indoor Dome		Wisenet X-plus series network IR varidial indoor camera, 6MP @ 30fps, motorized varifocal lens 3x (2.8-8.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 131.23', shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, IP67/IP68, K10, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNB-9002	6MP Box Camera		Wisenet X series network box camera, 6MP @ 30fps, triple code: H.265H/264 MJPEG with WiseStream II technology, Extreme WDR, USB and CVBS port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DN, dual SD cards slots, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/24VAC/PoE, -10°C ~ +55°C (-14°F ~ +131°F)
5MP Cameras				
Camera - Network	XND-9081REV	5MP Indoor Dome, PoE extender camera	POE+ Required	Wisenet X powered by Wisenet 5 network IR indoor dome camera with PoE Extender, PoE+ in PoE out, 5MP @ 30fps, Motorized Varifocal Lens (3.9mm - 9.4mm), triple code: H.265H/264 MJPEG with WiseStream II technology, WDR 120dB, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, halway view, H.LC, defog detection, DIS(Gyro), PoE/PoE+, IP52, K10, -25°C ~ +60°C (-13°F ~ +140°F)
Camera - Network	XNV-9081RE	5MP Outdoor Dome, PoE extender camera	POE+ Required	Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera with PoE Extender, PoE+ in PoE out, 5MP @ 30fps, Motorized Varifocal Lens (3.9mm - 9.4mm) (102°-38.7°), triple code: H.265H/264 MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, halway view, H.LC, defog detection, DIS(Gyro), PoE/PoE+, IP66/IP67/IP68, K10, NEMA4X, -50°C ~ +60°C (-58°F ~ +140°F)
Camera - Network	XNV-9081R	5MP IR Outdoor Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, 5MP @ 30fps, motorized varifocal lens 2.6x (3.6-9.4mm) (102°-38.7°), triple code: H.265H/264 MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true DN, dual SD card, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, 24VAC, IP67/IP68/IP68, K10+, Nema 4X, -50°C ~ +60°C (-58°F ~ +140°F), white color, very skin included, optional black skin cover
Camera - Network	XND-9081RV	5MP IR Indoor Dome		Wisenet X series Plus powered by Wisenet 5 network indoor vandal dome camera, modular structure, 5MP @ 30fps, motorized varifocal lens 2.6x (3.6-9.4mm) (102°-38.7°), triple code: H.265H/264 MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true DN, dual SD card, halway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, K10, white color, very skin included, optional black skin cover

Camera - Network	XND-8081RF	SMP IR Flush Mount Dome		Wisenet X series Plus powered by Wisenet 5 IR network indoor flush mount vandal dome camera, modular structure, SMP @ 30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (102°-38.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true D.N, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP69K, IK10, Nema 4X, 50°C ~ +60°C (-55°C ~ +140°C) white color (not included, optional black color)
Camera - Network	XNV-8081Z	SMP Outdoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network outdoor vandal dome camera, modular structure, SMP @ 30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (102°-38.7°), PTRZ, triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D.N, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP69K, IK10, Nema 4X, 50°C ~ +60°C (-55°C ~ +140°C) white color (not included, optional black color)
Camera - Network	XND-8081VZ	SMP Indoor PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, SMP @ 30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (102°-38.7°), PTRZ, triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D.N, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP69K, IK10, Nema 4X, 50°C ~ +60°C (-55°C ~ +140°C) white color (not included, optional black color)
Camera - Network	XND-8081FZ	SMP Flush Mount PTRZ Dome		Wisenet X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, SMP @ 30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (102°-38.7°), PTRZ, triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true D.N, dual SD card, hallway view, H.LC, defog detection, DIS (Gyro), 12VDC/PoE, IP67, IP69K, IK10, Nema 4X, 50°C ~ +60°C (-55°C ~ +140°C) white color (not included, optional black color)
Camera - Network	XNF-8010R	X-Series Indoor IR Fisheye		Wisenet X powered by Wisenet 5 network indoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, 12VDC/PoE
Camera - Network	XNF-8010RW	X-Series Indoor IR Fisheye (White Color)		Wisenet X powered by Wisenet 5 network indoor fisheye (white color), 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, 12VDC/PoE, white color
Camera - Network	XNF-8010RV	X-Series Outdoor IR Fisheye		Wisenet X powered by Wisenet 5 network outdoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, 12VDC/PoE, IP66, IK10, -55°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNF-8010RVm	X-Series Mobile IR Fisheye		Wisenet X powered by Wisenet 5 network mobile vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49', simple focus, dual SD card, H.LC, defog detection, DIS, Fx Mobile Application (MTC Connector) RJ45 to M12 adapter is NOT included, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-8080RSA	SMP Stainless Steel IR Dome	IP69K	Wisenet X powered by Wisenet 5 network IR stainless steel dome camera, SMP @30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (92°-1~38.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67/IP69K, IK10, Nema 4X, IP69K, (MTC ~45°C (-40°F ~ +131°F))
Camera - Network	XNV-8080R	SMP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (92°-1~38.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/24VAC/PoE, IP67, IP69K, Nema 4X, -55°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-8020R	SMP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @30fps, 3.7mm fixed focal lens (97.5°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNV-8030R	SMP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @30fps, 4.6mm fixed focal lens (77.9°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNV-8040R	SMP IR Outdoor Dome		Wisenet X powered by Wisenet 5 network IR outdoor vandal dome camera, SMP @30fps, 7mm fixed focal lens (50.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP67, IK10
Camera - Network	XNO-8080R	SMP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (100°-2~38.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 164', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/24VAC/PoE, IP67, IK10, Nema 4X, -55°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNO-8020R	SMP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @30fps, 3.7mm fixed focal lens (97.5°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XNO-8030R	SMP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @30fps, 4.6mm fixed focal lens (77.9°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XNO-8040R	SMP IR Bullet		Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, SMP @30fps, 7mm fixed focal lens (50.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, backdoor included, 12VDC/PoE, IP67, IK10, Nema 4X
Camera - Network	XND-8080RV	SMP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @30fps, motorized varifocal lens 2.4x (3.9-9.4mm) (92°-1~38.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP68
Camera - Network	XND-8020R	SMP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @30fps, 3.7mm fixed focal lens (97.5°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP68
Camera - Network	XND-8030R	SMP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @30fps, 4.6mm fixed focal lens (77.9°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP68
Camera - Network	XND-8040R	SMP Indoor IR Vandal Dome		Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, SMP @30fps, 7mm fixed focal lens (50.7°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true D.N, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IP68
Camera - Network	XND-8020F	SMP Flush Mount		Wisenet X powered by Wisenet 5 network flush mount dome camera, SMP @ 30fps, 3.7mm fixed lens (97.5°), triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic DIN, SD card, hallway view, H.LC, defog detection, DIS, PoE only
Camera - Network	XNB-8000	SMP Box		Wisenet X powered by Wisenet 5 network box camera, SMP @30fps, simple focus, triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true D.N, dual SD card, hallway view, H.LC, defog detection, DIS (Using a Gyro sensor), 12VDC/24VAC/PoE
Camera - Network	XNO-8010R	SMP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	XNO-8020R	SMP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, 4.0mm fixed focal lens (79°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 62', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	XNO-8030R	SMP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, 6.0mm fixed focal lens (49°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	QNO-8080R	SMP IR Bullet		Wisenet Q network outdoor vandal bullet camera, SMP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (100°-31°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	QNV-8010R	SMP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QNV-8020R	SMP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, 4.0mm fixed focal lens (79°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 82', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QNV-8030R	SMP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, 6.0mm fixed focal lens (49°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QNV-8080R	SMP IR Outdoor Dome		Wisenet Q network outdoor vandal dome camera, SMP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (100°-31°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE, white color
Camera - Network	QND-8010R	SMP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8020R	SMP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, 4.0mm fixed focal lens (79°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8030R	SMP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, 6.0mm fixed focal lens (49°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8080R	SMP Indoor IR Dome		Wisenet Q network indoor dome camera, SMP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (100°-31°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8011	SMP Indoor Dome		Wisenet Q mini network indoor dome camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QND-8021	SMP Indoor Dome		Wisenet Q mini network indoor dome camera, SMP @ 30fps, 4.0mm fixed focal lens (80°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QNE-8011R	SMP IR Outdoor Flat-Eye		Wisenet Q mini network outdoor fisheye camera, SMP @ 30fps, 2.8mm fixed focal lens (104°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP67, IK10, PoE, white color
Camera - Network	QNE-8021R	SMP IR Outdoor Flat-Eye		Wisenet Q mini network outdoor fisheye camera, SMP @ 30fps, 4.0mm fixed focal lens (80°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, IP67, IK10, PoE, white color
Camera - Network	QNF-8010	6MP Indoor fisheye		Wisenet Q series network indoor fisheye dome camera, 6MP CMOS sensor, max resolution 2048x2048 @ 30fps, triple code H.265H.264MJPEG with Wisestream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE
Camera - Network	TNV-8010C	SMP Compact corner mount camera	Limited Stock	Compact corner mount camera, SMP @ 30fps, triple code, WDR 120dB 2.3mm fixed, USB and CVBS, true D.N, SD cards slots, hallway view, H.LC, defog detection, PoE, Audio-in/Audio-out, Wisenet open platform IP66, IP69K, IK10, video analytics - Defocus, Directional, Motion, Enter/Exit, Tampering, Virtual line, Audio
4MP Cameras				
Camera - Network	QND-7082R	4MP IR Dome		Wisenet Q network indoor dome camera, 4MP @30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33.2°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 20m (65.62'), Motion detection, Tampering, Defocus detection, Hallway View, LDC support, Built-in mic (One way audio), Micro SD/SDHC/SDXC card 1 slot (Max 128GB), PoE/12VDC (White color)
Camera - Network	QNV-7082R	4MP IR Vandal Dome		Wisenet Q network outdoor vandal dome camera, 4MP @30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33.2°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway View, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max 128GB), IP66, IK10, PoE/12VDC (White color)
Camera - Network	QNO-7082R	4MP IR Bullet		Wisenet Q network outdoor vandal bullet camera, 4MP @30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33.2°), triple code H.265H.264MJPEG with Wisestream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway View, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max 128GB), IP66, IK10, PoE/12VDC
3MP Cameras				
Camera - Network	TNV-7010RC	3MP IR Vandal Corner Camera	Limited Stock	Wisenet T powered by Wisenet 5 network outdoor IR corner mount camera, SMP 2048x1536 @ 30fps, 2.8mm fixed lens (102°/75°), 940mm IR 32', built-in mic, triple code H.265H.264MJPEG with Wisestream II technology, 120dB WDR, advanced video analytics and business analytics, simple SD card, H.LC, defog detection, DIS, PoE, IP66, Nema 4X, IK10
2MP Cameras				
Camera - Network	PND-A6081RF	2MP IR Indoor Flush Mount Dome AI Camera		2MP Network AI IR Dome Camera, Max 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m (131.23m), Wise IR, Day & Night (ICR), WDR (120dB), WisenRTR (Using AI engine), H.265, H.264, MJPEG, Wisestream II, WisestreamIII (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate)), Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Plenum rate, Modular structure for easy instal, Built-in mic
Camera - Network	PND-A6081RV	2MP IR Indoor Vandal Dome AI Camera		2MP Network AI IR Dome Camera, Max 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m (131.23m), Wise IR, Day & Night (ICR), WDR (120dB), WisenRTR (Using AI engine), H.265, H.264, MJPEG, Wisestream II, WisestreamIII (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate)), Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble, IP52, IK10, Modular structure for easy instal, PoE
Camera - Network	PNV-A6081R	2MP IR Outdoor Vandal Dome AI Camera		2MP Network AI IR Vandal Dome Camera, Max 2MP resolution, Up to 120fps, 0.007Lux@F1.3 (Color), 0Lux (B/W, IR LED on), IR Viewable Length 40m (131.23m), Wise IR, Day & Night (ICR), WDR (120dB), WisenRTR (Using AI engine), H.265, H.264, MJPEG, Wisestream II, WisestreamIII (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate)), Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 level2, Secure boot, Verify firmware forgery, Hard-coated dome bubble/IP67, IP69K, IK10, NEMA4, Modular structure for easy instal, PoE

Camera - Network	XND-6080V	2MP Indoor Vandal Dome	Wisetnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized varifocal lens 3.1x (2.8-12mm) (119.5°-27.9°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6010	2MP Indoor Vandal Dome	Wisetnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6020R	2MP Indoor IR Vandal Dome	Wisetnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 4mm fixed lens (88.8°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, IK08
Camera - Network	XND-6011F	2MP Flush Mount	Wisetnet X powered by Wisenet 5 network flush mount dome camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (112°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Mic, magnetic cover, electronic DIN, SD card, hallway view, H.LC, defog detection, DIS, PoE only
Camera - Network	XNV-6013M	2MP Mobile Vandal Dome	This camera is designed to be mounted outside of the vehicle. M12 connector (M12 to BNC) is included. Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, -40°C ~ +60°C (-40°F ~ +140°F)
Camera - Network	XNV-6012	2MP Mobile Vandal Dome	Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNV-6012M	2MP Mobile Vandal Dome	Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (135.4°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNV-6022R	2MP Mobile Vandal Dome	Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X
Camera - Network	XNV-6022RM	2MP Mobile Vandal Dome	Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, 3.6mm fixed lens (94.8°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNZ-6320	2MP 32x Zoom Box	Wisetnet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32x optical zoom lens (4.4mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, USB port for easy installation, advanced video analytics and sound classification, true DIN, dual SD card, H.LC, defog detection, DIS(Gyro), 12VDC/PoE
Camera - Network	XNZ-6320	2MP 32x Zoom Box	Wisetnet X powered by Wisenet 5 network zoom box camera, 2MP, Full HD(1080p) @60fps, 32x optical zoom lens (4.4mm ~ 142.6mm) (61.8° ~ 2.19°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, advanced video analytics and sound classification, true DIN, built-in SD card slot, H.LC, defog detection, 12VDC/PoE
Camera - Network	XNB-6000	2MP Box	Wisetnet X powered by Wisenet 5 network box camera, 2MP, Full HD(1080p) @60fps, simple focus, triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DIN, dual SD card, hallway view, H.LC, defog detection, DIS(Gyro), 12VDC/24VAC/PoE
Camera - Network	XNB-6001	2MP Covert Camera Main Module	Wisetnet X powered by Wisenet 5 covert camera body, 2MP, Full HD(1080p) @60fps, triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14° ~ 131°, lens module is not included Compatible lens modules (SLA-T6800, SLA-T6800, SLA-T6800, SLA-T6800, SLA-T6800, SLA-T6800, SLA-T6800, SLA-T6800)
Camera - Network	XNV-16080R	2MP IR Outdoor Dome	Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°-33.2°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, USB port for easy installation, high powered IR LEDs range of 98.43, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XNV-16090	2MP Outdoor Dome	Wisetnet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°-33.2°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, USB port for easy installation, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XND-16080RV	2MP Indoor IR Vandal Dome	Wisetnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°-33.2°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, USB port for easy installation, high powered IR LEDs range of 98.43, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	XND-16080V	2MP Indoor Vandal Dome	Wisetnet X powered by Wisenet 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°-33.2°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, USB port for easy installation, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IK08
Camera - Network	XNO-16080R	2MP IR Bullet	Wisetnet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°-33.2°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, USB port for easy installation, high powered IR LEDs range of 98.43, true DIN, single SD card, hallway view, H.LC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)
Camera - Network	TNB-6030	PVM Camera	PVM camera powered by Wisenet 5, 1080p (1920x1080), micro HDMI output, 16:9 aspect ratio, face detection applied for visual deterrent, customizable text overlay, 4.6mm fixed lens (7.8°), 1505B WDR, H.265H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, built-in defog detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	TNO-6010M	Front Facing Bullet	Wisetnet T network mobile front facing camera, 2MP @ 60fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1505B WDR, USB port for easy installation, advanced video analytics, true DIN, SD card, hallway view, H.LC, defog detection, DIS (Gyro), PoE, IP66, IK10, M12 connector (M12 to BNC) is not included
Camera - Network	QNO-6012R	2MP IR Bullet	Wisetnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 65', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6012R1	2MP IR Bullet	Wisetnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 65', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6022R	2MP IR Bullet	Wisetnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 82', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6032R	2MP IR Bullet	Wisetnet Q network outdoor vandal bullet camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-6082R	2MP IR Bullet	Wisetnet Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6012R	2MP IR Outdoor Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 65', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6012R1	2MP IR Outdoor Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 65', defocus detection, hallway view, no audio input, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6022R	2MP IR Outdoor Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 82', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6024RM	2M Mobile IR Flat Camera	Wisetnet Q network mobile IR vandal dome camera, 2MP, Full HD(1080p) @30fps, triple codec H.265H.264/MJPEG with WiseStream II technology, Fixed focal lens (M12 connector RJ45 adapter is not included), hallway view, one way audio and SD card, video analytics, CVBS, open platform, 1205B WDR, built-in IR range of 37.8', true DIN, built-in SD card slot, IP66, IK10
Camera - Network	QNV-6032R	2MP IR Outdoor Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6082R	2MP IR Outdoor Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6082R1	2MP IR Outdoor Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, no audio input, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNV-6023R	2MP IR Vandal Dome	Wisetnet Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 49', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	QND-6012R	2MP IR Indoor Dome	Wisetnet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 65', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC
Camera - Network	QND-6012R1	2MP IR Indoor Dome	Wisetnet Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 65', defocus detection, hallway view, no audio input, SD card, video analytics, CVBS, open platform, PoE/12VDC
Camera - Network	QND-6022R	2MP IR Indoor Dome	Wisetnet Q network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 82', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC
Camera - Network	QND-6032R	2MP IR Indoor Dome	Wisetnet Q network indoor dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (52°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC
Camera - Network	QND-6082R	2MP IR Indoor Dome	Wisetnet Q network indoor dome camera, 2MP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC
Camera - Network	QND-6082R1	2MP IR Indoor Dome	Wisetnet Q network indoor dome camera, 2MP @ 30fps, motorized varifocal lens 3.1x (3.2 ~ 10.0mm) (109°-33°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, IR LEDs range 98', defocus detection, hallway view, no audio input, SD card, video analytics, CVBS, open platform, PoE/12VDC
Camera - Network	QND-6011	2MP Indoor Dome	Wisetnet Q mini network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, defocus detection, hallway view, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QND-6021	2MP Indoor Dome	Wisetnet Q mini network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple codec H.265H.264/MJPEG with WiseStream II, 1205B WDR, defocus detection, hallway view, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	JNV-6072R	2MP IR Vandal Dome	J series outdoor vandal dome camera, 2MP @ 30fps, varifocal lens 3.1x (3.2 ~ 10.0mm) (101.6° ~ 31.1°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs range 82', defocus detection, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	JNV-6012R	2MP IR Vandal Dome	J series outdoor vandal dome camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	JNV-6022R	2MP IR Vandal Dome	J series outdoor vandal dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	JNV-6032R	2MP IR Vandal Dome	J series outdoor vandal dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	JND-6072R	2MP IR Dome	J series indoor dome camera, 2MP @ 30fps, varifocal lens 3.1x (3.2 ~ 10mm) (101.6° ~ 31.1°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	JND-6012R	2MP IR Dome	J series indoor dome camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	JND-6022R	2MP IR Dome	J series indoor dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	JND-6032R	2MP IR Dome	J series indoor dome camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	JNO-6012R	2MP IR Bullet	J series outdoor bullet camera, 2MP @ 30fps, varifocal lens 3.1x (3.2 ~ 10mm) (101.6° ~ 31.1°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	JNO-6012R1	2MP IR Bullet	J series outdoor bullet camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	JNO-6022R	2MP IR Bullet	J series outdoor bullet camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	JNO-6032R	2MP IR Bullet	J series outdoor bullet camera, 2MP @ 30fps, 6mm fixed focal lens (51°), Double codec H.264/MJPEG, WiseStream II, 1205B WDR, IR LEDs, hallway view, SD card, IP66, PoE, White
Camera - Network	XNB-H6241A	2MP Network ATM Camera Kit	Wisetnet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14° ~ 131°, cable length is 5m (26 feet)
Camera - Network	XNB-H6240A	2MP Network ATM Camera Kit	Wisetnet X powered by Wisenet 5 network ATM camera, 2MP, Full HD(1080p) @60fps, 2.4mm fixed lens (139°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14° ~ 131°, cable length is 1.5m (4.9 feet)
Camera - Network	XNB-H6461H	2MP Pinhole Height Strip Camera Kit	Wisetnet X powered by Wisenet 5 network pinhole camera with height strip housing, 2MP, Full HD(1080p) @60fps, 4.6mm fixed lens (73°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14° ~ 131°, cable length is 8m (26 feet)
Camera - Network	XNB-H6280B	2MP Bandit Barrier	Wisetnet X powered by Wisenet 5 network Bandit Barrier camera, 2MP, Full HD(1080p) @60fps, 2.8mm fixed lens (107°), triple codec H.265H.264/MJPEG with WiseStream II technology, 1205B WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defog detection, DIS, 12VDC/PoE, +14° ~ 131°, cable length is 1.5m (4.9 feet)
Camera - Network	QNP-6230	2MP 23x PTZ	Wisetnet Q network outdoor PTZ camera, 2MP, Full HD(1080p) @30fps, H.265H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 1205B WDR, true DIN, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE+
Camera - Network	QNP-6250H	2MP 25x PTZ	Wisetnet Q network outdoor PTZ camera, 2MP, Full HD(1080p) @30fps, triple codec H.265H.264/MJPEG with WiseStream II technology, 4.4x-111mm (25x) lens, 1205B WDR, Day & Night (ICR), 8x SRS (Ball-in-gyro) sensor, Micro SD/SDHC/SDXC, built-in 256GB Focus Stack, IP66, IK10, NEMA4X, white color
Camera - Network	QNP-6230H	2MP 23x PTZ	Wisetnet Q network outdoor PTZ camera, 2MP, Full HD(1080p) @30fps, H.265H.264/MJPEG, Optical Zoom Lens 23x (4.44-102.1mm), 1205B WDR, true DIN, 500°/sec Pan, SD/SDHC/SDXC, 24VAC/PoE, Analytics, IP66, IK10, Heater on, 58° F 24VAC
Camera - Network	QNP-6230RH	2MP IR 23x PTZ	Wisetnet Q network outdoor IR PTZ camera, 2MP for up to 328R, 2MP, Full HD(1080p) @30fps, triple codec H.265H.264/MJPEG with WiseStream II, 23x optical zoom (4.4 ~ 102.1mm) (61° ~ 3.89°), 1205B WDR, H.LC, true DIN, 24VAC/HPRE, IP66, IK10, Built-in 58° F 50° C Heater (24VAC only) HPE IR projector not included
Camera - Network	TNU-621	2MP 32x Positioning Camera	Wisetnet Network Positioning Camera (1920 x 1080 resolution), 4.44 ~ 142.6mm (120x) varifocal lens, 300fps/2MP (MJPEG), H.265, H.264, M.JPEG codes support, 360° E-pan, 4x 8x, 120° WDR, H.LC, Defog, Tampering, Virtual lens, Enter / Exit, (Dis)Appear, Audio detection, Face detection, Motion detection, micro SD / SDHC / SDXC slot, Power 24VAC (Optional IR Illuminators: 8P/50)

Thermal Cameras

Lens	SLA-T4680VA	4.6mm Lens/Imager right angle body for PNM-9000QB (8.0m cable)		4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480A	2.4mm Lens/Imager straight body for PNM-9000QB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480VA	2.4mm Lens/Imager right angle body for PNM-9000QB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T1080FA	1.6mm Lens/Imager straight body for PNM-9000QB (8.0m cable)		1.6mm fixed lens module, compatible with PNM-9000QB, straight body style, 2MP @ 30fps, 0.03 Lux, 187° horizontal field of view, 8 meters cable/ 26 feet cable
Lens	SLA-H-4680VA	Height strip with 2MP pinhole lens	Camera not included	Height strip with 4.6mm pinhole lens module, compatible with PNM-9000QB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680D	Door Jamb Lens (black)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, black color
Lens	SLA-T4680DS	Door Jamb Lens (silver)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, silver color
Lens	SLA-T4680DW	Door Jamb Lens (white) Special order ONLY	Special order only	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, white color
Lens	SLA-T-M410DN	Megapixel DC-iris Lens		Megapixel lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (4-10mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001
Lens	SLA-T-M1250DN	Megapixel DC-iris Lens		Megapixel lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (12-50mm), DC auto iris, CS-Mount, Compatible with: XNB-6005/8000, PNB-A9001
Lens	SLA-T-M840DN	Megapixel DC-iris Lens		Lens, 1/2.3" Up to 4K Vari-focal(9-40mm), Auto DC IRIS, CS-Mount, compatible with: XNB-6000, HCB-6000/6017/7000/7000A
Lens	SLA-2M240P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M280P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M360P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M600P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M120P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/2.8" 2MP CMOS with a 12.0mm fixed focal lens, FoV: H: 26.3°, V: 14.9°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M370P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M460P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M700P	PNM-9320VQP Lens module	For the PNM-9320VQP, PNM-9321VQP	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M240Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-9000VQ
Lens	SLA-2M280Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9000VQ
Lens	SLA-2M360Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9000VQ
Lens	SLA-2M600Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9000VQ
Lens	SLA-5M370Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9°, for the PNM-9000VQ
Lens	SLA-5M460Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9°, for the PNM-9000VQ
Lens	SLA-5M700Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8°, for the PNM-9000VQ
Lens	SLA-5M460D	PNM-9000VQ Lens module	For the PNM-9000VQ	1/1.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9°, for the PNM-9000VQ
Lens	SLA-5M700D	PNM-9000VQ Lens module	For the PNM-9000VQ	1/1.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8°, for the PNM-9000VQ
Lens	SLA-2M240D	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7000VQ
Lens	SLA-2M280D	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7000VQ
Lens	SLA-2M360D	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7000VQ
Lens	SLA-2M600D	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7000VQ
Lens	SLA-2M240ZD	PNM-7002VQ Lens module	For the PNM-7002VQ	1/2.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7002VQ
Lens	SLA-2M280ZD	PNM-7002VQ Lens module	For the PNM-7002VQ	1/2.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7002VQ
Lens	SLA-2M360ZD	PNM-7002VQ Lens module	For the PNM-7002VQ	1/2.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7002VQ
Lens	SLA-2M600ZD	PNM-7002VQ Lens module	For the PNM-7002VQ	1/2.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7002VQ
Lens	SLA-M2890DN	Megapixel DC-iris Lens		Lens, 1/2.3" 3MP, Vari-focal (2.8-9.0mm), Auto DC Iris, CS-Mount
Lens	SLA-M2990PN	Megapixel P-Iris Lens		Lens, 1/2.3" 3MP, Vari-focal (2.8-9.0mm), Auto P Iris, CS-Mount
Lens	SLA-T-M1250DN	Megapixel DC-iris Lens		Lens, 1/1.8" 6MP, Vari-focal (4.1-9mm), Auto DC Iris, CS-Mount
Lens	SLA-T-M1250DN	Megapixel DC-iris Lens		Lens, 1/2.3" 3MP, Vari-focal (11.5-50mm), Auto DC Iris, CS-Mount, Tele Range 3.3x
Accessories				
Accessory	SPM-4210	Network I/O Box		Network I/O Box for PTZ plus, 4-configurable I/O ports, Audio I/O, PoE. Compatible with XNP-9300RW/9250R/9250 XNP-9300RW/9250R/9250 XNP-9300M/9300M
Accessory	SBD-120CP	Gangbox Plate		Adapter plate for Single, Double, X Design, supported cameras (QND-8070R/7080R, LND-6017R/6072R, HCD-7010R/7020R/7030R/7030R) Pack of 5
Accessory	SBD-110GP	Gangbox Plate		Adapter plate for Single, Double, X Design, supported cameras (7010R/7020R/7030R, QND-8010/8020R/8030R/8040R, 8012R/8022R/8032R, HCD-7010RA/7020RA/7030RA) Pack of 5
Accessory	SBP-B-100P	Gang Box Plate		Single Gang Box Converter Plate for XNV-6011
Accessory	TR-6000	ATM mounting bracket		ATM mounting bracket for remote head lens
Accessory	SBP-279HM	Cap Adapter		Cap adapter for the PNM-9000VQ and PNM-9003VQ
Accessory	SBP-329HM	Cap Adapter		Large Cap adapter (outdoor) for the Multi-Directional cameras PNM-9080VQ and PNM-9081VQ (Will fit the following accessories: SBP-300WM, SBP-300LM, SBP-300CM) (Will not fit the SBP-300WM)
Accessory	SBP-317HM	Cap Adapter		Large cap adapter (indoor) for the PNM-9320VQP and PNM-9321VQP and PNM-9322VQ (Will fit the following accessories: SBP-300WM, SBP-300LM, SBP-300CM, SBP-300M, SBP-300V, SBP-300M, SBP-300M)
Accessory	SBP-301HM	Cap Adapter		Cap Adapter for the PNM-9000VQ Multi-Sensor
Accessory	SBP-301HMV	Cap Adapter		Cap Adapter for the PNM-9000VQ Multi-Sensor
Accessory	SBP-303HM	Cap Adapter		Cap Adapter for the PNM-9080R, XND-8080R, XND-8080V, XND-8081R, XND-8081V, XND-8082R, XND-8082V, XND-8083R, XND-8083V, XND-8084R, XND-8084V, XND-8085R, XND-8085V, XND-8086R, XND-8086V, XND-8087R, XND-8087V, XND-8088R, XND-8088V, XND-8089R, XND-8089V, XND-8090R, XND-8090V, XND-8091R, XND-8091V, XND-8092R, XND-8092V, XND-8093R, XND-8093V, XND-8094R, XND-8094V, XND-8095R, XND-8095V, XND-8096R, XND-8096V, XND-8097R, XND-8097V, XND-8098R, XND-8098V, XND-8099R, XND-8099V, XND-8100R, XND-8100V, XND-8101R, XND-8101V, XND-8102R, XND-8102V, XND-8103R, XND-8103V, XND-8104R, XND-8104V, XND-8105R, XND-8105V, XND-8106R, XND-8106V, XND-8107R, XND-8107V, XND-8108R, XND-8108V, XND-8109R, XND-8109V, XND-8110R, XND-8110V, XND-8111R, XND-8111V, XND-8112R, XND-8112V, XND-8113R, XND-8113V, XND-8114R, XND-8114V, XND-8115R, XND-8115V, XND-8116R, XND-8116V, XND-8117R, XND-8117V, XND-8118R, XND-8118V, XND-8119R, XND-8119V, XND-8120R, XND-8120V, XND-8121R, XND-8121V, XND-8122R, XND-8122V, XND-8123R, XND-8123V, XND-8124R, XND-8124V, XND-8125R, XND-8125V, XND-8126R, XND-8126V, XND-8127R, XND-8127V, XND-8128R, XND-8128V, XND-8129R, XND-8129V, XND-8130R, XND-8130V, XND-8131R, XND-8131V, XND-8132R, XND-8132V, XND-8133R, XND-8133V, XND-8134R, XND-8134V, XND-8135R, XND-8135V, XND-8136R, XND-8136V, XND-8137R, XND-8137V, XND-8138R, XND-8138V, XND-8139R, XND-8139V, XND-8140R, XND-8140V, XND-8141R, XND-8141V, XND-8142R, XND-8142V, XND-8143R, XND-8143V, XND-8144R, XND-8144V, XND-8145R, XND-8145V, XND-8146R, XND-8146V, XND-8147R, XND-8147V, XND-8148R, XND-8148V, XND-8149R, XND-8149V, XND-8150R, XND-8150V, XND-8151R, XND-8151V, XND-8152R, XND-8152V, XND-8153R, XND-8153V, XND-8154R, XND-8154V, XND-8155R, XND-8155V, XND-8156R, XND-8156V, XND-8157R, XND-8157V, XND-8158R, XND-8158V, XND-8159R, XND-8159V, XND-8160R, XND-8160V, XND-8161R, XND-8161V, XND-8162R, XND-8162V, XND-8163R, XND-8163V, XND-8164R, XND-8164V, XND-8165R, XND-8165V, XND-8166R, XND-8166V, XND-8167R, XND-8167V, XND-8168R, XND-8168V, XND-8169R, XND-8169V, XND-8170R, XND-8170V, XND-8171R, XND-8171V, XND-8172R, XND-8172V, XND-8173R, XND-8173V, XND-8174R, XND-8174V, XND-8175R, XND-8175V, XND-8176R, XND-8176V, XND-8177R, XND-8177V, XND-8178R, XND-8178V, XND-8179R, XND-8179V, XND-8180R, XND-8180V, XND-8181R, XND-8181V, XND-8182R, XND-8182V, XND-8183R, XND-8183V, XND-8184R, XND-8184V, XND-8185R, XND-8185V, XND-8186R, XND-8186V, XND-8187R, XND-8187V, XND-8188R, XND-8188V, XND-8189R, XND-8189V, XND-8190R, XND-8190V, XND-8191R, XND-8191V, XND-8192R, XND-8192V, XND-8193R, XND-8193V, XND-8194R, XND-8194V, XND-8195R, XND-8195V, XND-8196R, XND-8196V, XND-8197R, XND-8197V, XND-8198R, XND-8198V, XND-8199R, XND-8199V, XND-8200R, XND-8200V, XND-8201R, XND-8201V, XND-8202R, XND-8202V, XND-8203R, XND-8203V, XND-8204R, XND-8204V, XND-8205R, XND-8205V, XND-8206R, XND-8206V, XND-8207R, XND-8207V, XND-8208R, XND-8208V, XND-8209R, XND-8209V, XND-8210R, XND-8210V, XND-8211R, XND-8211V, XND-8212R, XND-8212V, XND-8213R, XND-8213V, XND-8214R, XND-8214V, XND-8215R, XND-8215V, XND-8216R, XND-8216V, XND-8217R, XND-8217V, XND-8218R, XND-8218V, XND-8219R, XND-8219V, XND-8220R, XND-8220V, XND-8221R, XND-8221V, XND-8222R, XND-8222V, XND-8223R, XND-8223V, XND-8224R, XND-8224V, XND-8225R, XND-8225V, XND-8226R, XND-8226V, XND-8227R, XND-8227V, XND-8228R, XND-8228V, XND-8229R, XND-8229V, XND-8230R, XND-8230V, XND-8231R, XND-8231V, XND-8232R, XND-8232V, XND-8233R, XND-8233V, XND-8234R, XND-8234V, XND-8235R, XND-8235V, XND-8236R, XND-8236V, XND-8237R, XND-8237V, XND-8238R, XND-8238V, XND-8239R, XND-8239V, XND-8240R, XND-8240V, XND-8241R, XND-8241V, XND-8242R, XND-8242V, XND-8243R, XND-8243V, XND-8244R, XND-8244V, XND-8245R, XND-8245V, XND-8246R, XND-8246V, XND-8247R, XND-8247V, XND-8248R, XND-8248V, XND-8249R, XND-8249V, XND-8250R, XND-8250V, XND-8251R, XND-8251V, XND-8252R, XND-8252V, XND-8253R, XND-8253V, XND-8254R, XND-8254V, XND-8255R, XND-8255V, XND-8256R, XND-8256V, XND-8257R, XND-8257V, XND-8258R, XND-8258V, XND-8259R, XND-8259V, XND-8260R, XND-8260V, XND-8261R, XND-8261V, XND-8262R, XND-8262V, XND-8263R, XND-8263V, XND-8264R, XND-8264V, XND-8265R, XND-8265V, XND-8266R, XND-8266V, XND-8267R, XND-8267V, XND-8268R, XND-8268V, XND-8269R, XND-8269V, XND-8270R, XND-8270V, XND-8271R, XND-8271V, XND-8272R, XND-8272V, XND-8273R, XND-8273V, XND-8274R, XND-8274V, XND-8275R, XND-8275V, XND-8276R, XND-8276V, XND-8277R, XND-8277V, XND-8278R, XND-8278V, XND-8279R, XND-8279V, XND-8280R, XND-8280V, XND-8281R, XND-8281V, XND-8282R, XND-8282V, XND-8283R, XND-8283V, XND-8284R, XND-8284V, XND-8285R, XND-8285V, XND-8286R, XND-8286V, XND-8287R, XND-8287V, XND-8288R, XND-8288V, XND-8289R, XND-8289V, XND-8290R, XND-8290V, XND-8291R, XND-8291V, XND-8292R, XND-8292V, XND-8293R, XND-8293V, XND-8294R, XND-8294V, XND-8295R, XND-8295V, XND-8296R, XND-8296V, XND-8297R, XND-8297V, XND-8298R, XND-8298V, XND-8299R, XND-8299V, XND-8300R, XND-8300V, XND-8301R, XND-8301V, XND-8302R, XND-8302V, XND-8303R, XND-8303V, XND-8304R, XND-8304V, XND-8305R, XND-8305V, XND-8306R, XND-8306V, XND-8307R, XND-8307V, XND-8308R, XND-8308V, XND-8309R, XND-8309V, XND-8310R, XND-8310V, XND-8311R, XND-8311V, XND-8312R, XND-8312V, XND-8313R, XND-8313V, XND-8314R, XND-8314V, XND-8315R, XND-8315V, XND-8316R, XND-8316V, XND-8317R, XND-8317V, XND-8318R, XND-8318V, XND-8319R, XND-8319V, XND-8320R, XND-8320V, XND-8321R, XND-8321V, XND-8322R, XND-8322V, XND-8323R, XND-8323V, XND-8324R, XND-8324V, XND-8325R, XND-8325V, XND-8326R, XND-8326V, XND-8327R, XND-8327V, XND-8328R, XND-8328V, XND-8329R, XND-8329V, XND-8330R, XND-8330V, XND-8331R, XND-8331V, XND-8332R, XND-8332V, XND-8333R, XND-8333V, XND-8334R, XND-8334V, XND-8335R, XND-8335V, XND-8336R, XND-8336V, XND-8337R, XND-8337V, XND-8338R, XND-8338V, XND-8339R, XND-8339V, XND-8340R, XND-8340V, XND-8341R, XND-8341V, XND-8342R, XND-8342V, XND-8343R, XND-8343V, XND-8344R, XND-8344V, XND-8345R, XND-8345V, XND-8346R, XND-8346V, XND-8347R, XND-8347V, XND-8348R, XND-8348V, XND-8349R, XND-8349V, XND-8350R, XND-8350V, XND-8351R, XND-8351V, XND-8352R, XND-8352V, XND-8353R, XND-8353V, XND-8354R, XND-8354V, XND-8355R, XND-8355V, XND-8356R, XND-8356V, XND-8357R, XND-8357V, XND-8358R, XND-8358V, XND-8359R, XND-8359V, XND-8360R, XND-8360V, XND-8361R, XND-8361V, XND-8362R, XND-8362V, XND-8363R, XND-8363V, XND-8364R, XND-8364V, XND-8365R, XND-8365V, XND-8366R, XND-8366V, XND-8367R, XND-8367V, XND-8368R, XND-8368V, XND-8369R, XND-8369V, XND-8370R, XND-8370V, XND-8371R, XND-8371V, XND-8372R, XND-8372V, XND-8373R, XND-8373V, XND-8374R, XND-8374V, XND-8375R, XND-8375V, XND-8376R, XND-8376V, XND-8377R, XND-8377V, XND-8378R, XND-8378V, XND-8379R, XND-8379V, XND-8380R, XND-8380V, XND-8381R, XND-8381V, XND-8382R, XND-8382V, XND-8383R, XND-8383V, XND-8384R, XND-8384V, XND-8385R, XND-8385V, XND-8386R, XND-8386V, XND-8387R, XND-8387V, XND-8388R, XND-8388V, XND-8389R, XND-8389V, XND-8390R, XND-8390V, XND-8391R, XND-8391V, XND-8392R, XND-8392V, XND-8393R, XND-8393V, XND-8394R, XND-8394V, XND-8395R, XND-8395V, XND-8396R, XND-8396V, XND-8397R, XND-8397V, XND-8398R, XND-8398V, XND-8399R, XND-8399V, XND-8400R, XND-8400V, XND-8401R, XND-8401V, XND-8402R, XND-8402V, XND-8403R, XND-8403V, XND-8404R, XND-8404V, XND-8405R, XND-8405V, XND-8406R, XND-8406V, XND-8407R, XND-8407V, XND-8408R, XND-8408V, XND-8409R, XND-8409V, XND-8410R, XND-8410V, XND-8411R, XND-8411V, XND-8412R, XND-8412V, XND-8413R, XND-8413V, XND-8414R, XND-8414V, XND-8415R, XND-8415V, XND-8416R, XND-8416V, XND-8417R, XND-8417V, XND-8418R, XND-8418V, XND-8419R, XND-8419V, XND-8420R, XND-8420V, XND-8421R, XND-8421V, XND-8422R, XND-8422V, XND-8423R, XND-8423V, XND-8424R, XND-8424V, XND-8425R, XND-8425V, XND-8426R, XND-8426V, XND-8427R, XND-8427V, XND-8428R, XND-8428V, XND-8429R, XND-8429V, XND-8430R, XND-8430V, XND-8431R, XND-8431V, XND-8432R, XND-8432V, XND-8433R, XND-8433V, XND-8434R, XND-8434V, XND-8435

Monitor	SMT-2730PV	27" PVM Monitor (Black)	2 Weeks lead time. For orders greater than 80, apply 14 Weeks lead time	27" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265H.264/MJPEG, HDMI input, slide show & live video, power supply included (12VDC)
Monitor	SMT-2701PVM	27" IP PVM Monitor (Black)	Special order	27" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265H.264/MJPEG, WiseStream 4 compression technology, micro SD(SDHC/SDXC), bidirectional audio, ballsway, video mode
Monitor	SMT-2233	1080P 22" LED monitor		22" LED Monitor, 1080p (1920x1080), 2 BNC loop through, HDMI, 16:9 aspect ratio, Built-in Speaker (2W), Tempered Glass, VESA DPM Compatible
Monitor	SMT-1935	4.3 19" LED Monitor		19" LED Monitor, 600TVL (1280 x 1024), 2 BNC Loop Through, HDMI, VGA, 4:3 aspect ratio, Built-in Speaker (2X1W), VESA DPM Compatible
Monitor	SMT-1030PV	10" PVM monitor (Black)	2 Weeks lead time. For orders greater than 80, apply 14 Weeks lead time	10" IP public view monitor, 1080p (1920x1080), HDMI, VGA, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (75 x 75mm), black casing, face detection display for visual deterrent, 2MP IP camera built-in, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265H.264/MJPEG, slide show & live video, power supply included (12VDC) or PoE+ powered
Monitor Stand	SBM-4343	43" Desktop Stand		Single monitor desktop stand, compatible with SMT-4343 monitor, black color, 100x100 VESA mountable
Controllers				
Analog - Controller	SPC-2010	Controller		Controller, 3D joystick, 2 line text LCD display, built-in jog shuttle, up to 255 PTZ/zoom cameras, RS-485, DVR, supports Multi-protocol
Analog - Controller	SPC-1010	Controller		Controller, PTZ joystick controller, 2 line text LCD display, up to 255 PTZ/zoom cameras, RS-485
Analog - Controller	SPC-2020	Controller		Controller, USB 3.0 joystick
Power Supplies				
Power Supply	PWR-P-POE15	15W PoE Injector		PoE Injector, 15W, 10/100/1000Mbps Base-T, AC100-240V Input, 50/60Hz, 54VDC/0.3Amp Output, CE/FCC Compliant, LED Indicator for Power and Network, Operational Temperature 32°F ~ 104°F (0 ~ 40°C)
Power Supply	PWR-P-POE30	30W PoE+ Injector		PoE+ Injector, 30W, 10/100/1000Mbps Base-T, AC100-240V Input, 50/60Hz, 54VDC/0.6Amp Output, CE/FCC Compliant, LED Indicator for Power and Network, Operational Temperature 32°F ~ 104°F (0 ~ 40°C)
Power Supply	PWR-DR12033	DIN Rail Mounting 33W Hardened Power Supply		12VDC 33Watt (2.75A) DIN Rail High Temp Power Supply (-40°C to +71°C With -40°C Start-Up)
Power Supply	PWR-24AC-1-3-ULW	Outdoor 24 VAC		Power supply, 24 VAC, 1 Output, 3 Amper, Nema 4X Enclosure, UL Listed, 110V only
Power Supply	PWR-24AC-50V-ULS	Indoor 24 VAC		Power supply, 24VAC, 50VA, UL Listed, 110V only
Open Platform Application License				
Open Platform Application License	OP-A2FMD-01	Single Camera License		One Camera License for Face Mask Detection Open Platform Application from a2 Technology. To be installed on Compatible X-Series Cameras (XNB-6000,XNO-6080R, XNO-6010R, XNO-6080R, XNO-6120R,XNV-6080, XNV-6080R, XNV-6010, XNV-6020R, XNV-6120R, XNV-6120, XNV-6011,XND-6080, XND-6080R, XND-6080V, XND-6010, XND-6020R, XND-6011P)
Services				
Service	DIN-SSDA006/CO	On-site engineering service	Service per/Day	This is an on site engineering service that will be provided by one of Hanwha Technix B2B security division trained personnel for our STEP dealers to help configuring or training on product including cameras, recorders and software. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of this SKU
Service	DIN-SSDA003/CO	Professional Firmware Customization	Service per/Day	This is a professional firmware customization service that will be provided by Hanwha Technix B2B security R&D Division to provide valuable functions on our network cameras and network recorders. This SKU is for one day engineering cost. For more details please contact us by emailing protect@services@hanwha.com
Service	DIN-SSDA008/CO	Remote engineering service	Service per/Day	This is a remote engineering service that will be provided by a Hanwha Technix B2B security division trained personnel for our STEP dealers to help configure or train on product including cameras, recorders and software. A reliable phone connection and internet connection (for a connection to the surveillance system via a remote desktop software) is required to be provided by the STEP partner. This SKU is for one day, if multiple days are needed please reflect that by increasing the QTY of the SKU

Disclaimer:

We put our best effort and knowledge to maintain the accuracy of specifications and price. Should there be any discrepancies we reserve the right to follow our specifications and price set. Thanks for your understanding.